

SAFETY DATA SHEET

SDS REVISION DATE: June 15, 2015

GMS Industrial Supply, Inc. 212 Denn Lane, Virginia Beach, VA 23462 (855) GRN-OGER • www.GreenOger.com

Product ID: GMS1132A 24-Hour Emergency Telephone: 1-800-424-9300 CHEMTREC

1. Identification

Product number GMS1132A

Product identifier 11 OZ BRITE WORKS GMS1132A

Revision date 06-15-2015

GMS INDUSTRIAL SUPPLY INC. Company information

212 DENN LANE

VIRGINIA BEACH, VA 23462 United States

General Assistance 757-473-1467 Company phone

Emergency telephone US 1-800-424-9300

03 Version#

05-31-2015 Supersedes date **CLEANER** Recommended use Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 Health hazards Serious eye damage/eye irritation Category 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

OSHA defined hazards Not classified.

Label elements







Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes serious eye

irritation. May cause drowsiness or dizziness.

Precautionary statement

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open Prevention

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.

Wear eye protection/face protection.

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If inhaled: Response

Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical

advice/attention.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from Storage

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise

classified (HNOC)

Combustible.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Product name: 11 OZ BRITE WORKS GMS1132A

SDS US Product #: GMS1132A Version #: 03 Revision date: 06-15-2015 Issue date: 09-24-2014

Chemical name	Common name and synonyms	CAS number	%
White Mineral Oil (petroleum)		8042-47-5	40 - 60
Distillates, Petroleum, Hydrotreat	ed	64742-46-7	20 - 40
Acetone		67-64-1	10 - 20
Butane		106-97-8	2.5 - 10
Propane		74-98-6	2.5 - 10
Naphtha, Petroleum, Light Alkyla	e	64741-66-8	1 - 2.5
Other components below reportal	ole levels		0.1 - 1

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Ingestion

media

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Most important Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, symptoms/effects, acute and redness, swelling, and blurred vision. delayed

Indication of immediate Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. medical attention and special

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

treatment needed

Suitable extinguishing media Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire. Unsuitable extinguishing

Specific hazards arising from Contents under pressure. Pressurized container may explode when exposed to heat or flame.

During fire, gases hazardous to health may be formed. the chemical

Firefighters must use standard protective equipment including flame retardant coat, helmet with Special protective equipment face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

and precautions for firefighters

Fire fighting Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to equipment/instructions prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or

monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move Specific methods containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Extremely flammable aerosol. Combustible.

Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Values	3		
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Butane (CAS 106-97-8)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	

Biological limit values

ACGIH Biological Exposure Indices
Components Value Determinant Specimen Sampling Time

Acetone (CAS 67-64-1) 25 mg/l Acetone Urine *

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

air-supplied respirator.

Product name: 11 OZ BRITE WORKS GMS1132A

Product #: GMS1132A Version #: 03 Revision date: 06-15-2015 Issue date: 09-24-2014

^{* -} For sampling details, please see the source document.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas.
Form Aerosol.
Color Not available.
Odor Not available.
Odor threshold Not available.
pH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

552.13 °F (288.96 °C) estimated

range

Flash point -156.0 °F (-104.4 °C) PROPELLANT estimated

Evaporation rate Not available. Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower 1.3

1.3 % estimated

(%)

Flammability limit - upper

9 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 25 psig @70F estimated

Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water)

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

Decomposition temperature

Not available.

Not available.

Not available.

Other information

Viscosity

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 0.773 estimated

Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

Hazardous decomposition

Conditions to avoid

products

No hazardous decomposition products are known.

Product name: 11 OZ BRITE WORKS GMS1132A

Product #: GMS1132A Version #: 03 Revision date: 06-15-2015 Issue date: 09-24-2014

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects.

Components Species Test Results

Acetone (CAS 67-64-1)

<u>Acute</u>

Dermal

LD50 Guinea pig > 7426 mg/kg, 24 Hours

> 9.4 ml/kg, 24 Hours

Rabbit > 7426 mg/kg, 24 Hours

> 9.4 ml/kg, 24 Hours

Inhalation

LC50 Rat 55700 ppm, 3 Hours

132 mg/l, 3 Hours

50.1 mg/l

Oral

LD50 Rat 5800 mg/kg

2.2 ml/kg

Butane (CAS 106-97-8)

<u>Acute</u>

Inhalation

LC50 Mouse 1237 mg/l, 120 Minutes

52 %, 120 Minutes

Rat 1355 mg/l

Distillates, Petroleum, Hydrotreated Middle (CAS 64742-46-7)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat 7640 mg/m3, 4 Hours

Mist

LC50 Rat 1.72 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Naphtha, Petroleum, Light Alkylate (CAS 64741-66-8)

Acute

Dermal

LD50 Rabbit > 1900 mg/kg, 24 Hours

Inhalation

LC50 Rat > 5000 mg/m3, 4 Hours

> 4980 mg/m3

Product name: 11 OZ BRITE WORKS GMS1132A

Product #: GMS1132A Version #: 03 Revision date: 06-15-2015 Issue date: 09-24-2014

Components **Species Test Results** > 4980 mg/m3, 4 Hours > 4.96 mg/l, 4 Hours Oral 4820 mg/kg LD50 Rat Propane (CAS 74-98-6) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes Rat 1355 mg/l 658 mg/l/4h White Mineral Oil (petroleum) (CAS 8042-47-5) Acute Dermal LD50 Rabbit > 2000 mg/kg, 24 Hours Inhalation LC50 Rat 2.18 mg/l, 4 Hours Oral **LD50** Rat > 5000 mg/kg * Estimates for product may be based on additional component data not shown. Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Causes serious eye irritation. irritation Respiratory or skin sensitization Not a respiratory sensitizer. Respiratory sensitization Skin sensitization This product is not expected to cause skin sensitization. No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity mutagenic or genotoxic. This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity IARC Monographs. Overall Evaluation of Carcinogenicity Not listed. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not regulated. US. National Toxicology Program (NTP) Report on Carcinogens Not listed. Reproductive toxicity This product is not expected to cause reproductive or developmental effects. Specific target organ toxicity -May cause drowsiness and dizziness. single exposure Specific target organ toxicity -Not classified. repeated exposure Aspiration hazard May be fatal if swallowed and enters airways. 12. Ecological information **Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. **Test Results** Components **Species** Acetone (CAS 67-64-1) Aquatic Crustacea EC50 Water flea (Daphnia magna) 21.6 - 23.9 mg/l, 48 hours

Rainbow trout, donaldson trout

(Oncorhynchus mykiss)

Product name: 11 OZ BRITE WORKS GMS1132A

Fish

SDS US

4740 - 6330 mg/l, 96 hours

LC50

Components Species Test Results

Naphtha, Petroleum, Light Alkylate (CAS 64741-66-8)

Aquatic

Algae IC50 Algae 30000 mg/L, 72 Hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

 Acetone
 -0.24

 Butane
 2.89

 Propane
 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Special provisions N82
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards No. ERG Code 10L

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions. Packaging Exceptions

LTD QTY

UN1950

AEROSOLS

IMDG

UN number UN proper shipping name Transport hazard class(es)

> Class 2.1 Subsidiary risk Label(s) None

Packing group

Not applicable.

LTD QTY Not applicable.

Environmental hazards

Marine pollutant No. F-D, S-U **EmS**

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and

6532

Chemical Code Number

Acetone (CAS 67-64-1)

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Distillates, Petroleum, Hydrotreated Middle (CAS 64742-46-7)

Naphtha, Petroleum, Light Alkylate (CAS 64741-66-8)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region On inventory (yes/no)* Inventory name

Australia Australian Inventory of Chemical Substances (AICS)

No SDS US Country(s) or region Inventory name On inventory (yes/no)* Domestic Substances List (DSL) Canada Yes Canada Non-Domestic Substances List (NDSL) No China Inventory of Existing Chemical Substances in China (IECSC) No Europe European Inventory of Existing Commercial Chemical No Substances (EINECS) Europe European List of Notified Chemical Substances (ELINCS) No Inventory of Existing and New Chemical Substances (ENCS) Japan No Korea Existing Chemicals List (ECL) No New Zealand New Zealand Inventory No **Philippines** Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico

Yes

No

Other information, including date of preparation or last revision

09-24-2014 Issue date 06-15-2015 Revision date

Version # 03

The information provided in this Safety Data Sheet is correct to the best of our knowledge, Disclaimer

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).