



SAFETY DATA SHEET

SDS PREP DATE: 6/1/2022

SDS REVISION DATE: 6/1/2022

Product ID: GMS1129A

0011

GMS Industrial Supply, Inc
212 Denn Lane, Virginia Beach, VA 23462
(855) GRN-OGER • www.GreenOger.com

24-Hour Emergency Telephone : 1-800-424-9300 CHEMTREC

This Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this SDS must be given to the buyer or the information incorporated in your SDS.

Section 1: Company and Product Identification

GMS Industrial Supply, Inc.

212 Denn Lane,

Virginia Beach, VA 23462

24-Hour Emergency Telephone: (800) 424-9300 CHEMTREC

Product ID: GMS1129A

Product Name: Orange Blade

Intended Use: ELECTRICAL CLEANER

Section 2: Hazard(s) Identification

Product Signal Word: DANGER

Physical Hazard Classification: Flammable Aerosols, Category 1

Extremely flammable aerosol.

Physical Hazard Precautionary Statements:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Protect from sunlight.

Do not expose to temperatures exceeding 50 °C/122°F.



Health Hazard Classification(s):

Acute Toxicity - Oral - Level 5

Acute Toxicity - Dermal - Level 5

Acute Toxicity - Inhalation - Level 5

Skin Corrosion/Irritation -Level 3

Eye Damage/Irritation -Level 2B

Aspiration Hazard - Level 2



Health Hazard Statements:

May be harmful if swallowed.

May be harmful if swallowed and enters airways.

May be harmful in contact with skin.

Causes mild skin irritation.

Causes eye irritation.

May be harmful if inhaled.

First-Aid Statement(s):

IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.

IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER/doctor/physician if you feel unwell.

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Handling and Storage Statement(s):

Store locked up.

Exposure Control / Personal Protection Statement(s):

Wash hands and exposed areas thoroughly after handling.

Disposal Statement(s):

Dispose of contents/container in accordance with local regulations.

Section 3: Product Composition

	CAS#	% Range		PEL	TLV
HYDROTREATED LIGHT DISTILLATE	64742-47-8	30%	70%	NONE ESTABLISHED BY OSHA	NONE ESTABLISHED BY OSHA
HYDROCARBON PROPELLANT	68476-86-8	10%	25%	NO DATA	NO DATA
D-LIMONENE DISTILLATE	5989-27-5	10%	30%	NOT ESTABLISHED	NOT ESTABLISHED

Section 4: First-Aid Measures

IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.

IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER/doctor/physician if you feel unwell.

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

GENERAL: This material is an aspiration hazard and defats the skin. Breathing vapors of high concentrations may cause CNS depression.

EYE CONTACT: Slightly irritating but does not injure eye tissue.

SKIN CONTACT: Low order of toxicity. Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

INHALATION: High vapor/aerosol concentrations (greater than approximately 100 ppm) are irritating to the eyes and the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

INGESTION: Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly minimal toxicity.

PRECAUTIONS

SPECIAL PRECAUTIONS: Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

PERSONAL PROTECTION: For open systems where contact is likely, wear safety glasses with side shields, long sleeves, and chemical resistant gloves. Where concentrations in air may exceed the limits, work practice or other means of exposure reduction are not adequate, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.

VENTILATION: The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated.

Section 5: Fire-Fighting Measures

FIRE AND EXPLOSION HAZARDS: This product releases Flammable Vapors at well below ambient temperatures and readily forms flammable mixtures with air exposed to an ignition source. It will burn in the open or be explosive in confined spaces. Its vapors are heavier than air and may travel long distances to a point of ignition, and then flash back. Alkaline/chlorine gas mixtures have produced explosions.

EXTINGUISHING MEDIA: Dry Chemical. CO₂. Halogenated Extinguishing Agent. Stop Gas Flow.

SPECIAL FIREFIGHTING PROCEDURES: Gas fires should not be extinguished unless the gas flow can be stopped immediately. Allow the fire to burn itself out. If the source cannot be shut off immediately, all equipment and surfaces exposed to the fire should be cooled with water to prevent over-heating flash-backs, or explosions. Control fire until gas supply can be shut off. Use proper protective equipment. Use fresh air respirator when exposure to hazardous concentrations of toxic gases is possible.

FIRE FIGHTING: Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boiling over. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

Section 6: Accidental Release Measures

STEPS TO BE TAKEN IN CASE CONTAINER IS PUNCTURED AND MATERIAL IS RELEASED:

Clean up area by mopping or with absorbent materials and place in closed container for disposal. Consult Federal, State, and local disposal authorities.

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

Section 7: Handling and Storage

Store locked up.

VENTILATION REQUIREMENT: Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

EYES: Face shield and goggles or chemical goggles should be worn.

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

Section 8: Exposure Control / Personal Protection

Wash hands and exposed areas thoroughly after handling.

VENTILATION REQUIREMENT: Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

EYES: Face shield and goggles or chemical goggles should be worn.

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

Section 9: Product Properties

Flash Point (CCP): LVL 3 AEROSOL, PROPELLENT: -136°F

Boiling Point for Product: N/D

Vapor Pressure for Product: N/D

Vapor Density for Product: N/D

Specific Gravity: N/D

V.O.C.: <50%

Water Solubility: NIL

Appearance: AEROSOL SPRAY

PH: N/D

Section 10: Stability and Reactivity

STABILITY: Stable

CONDITIONS TO AVOID: Temperatures above 130 degree F.

HAZARDOUS POLYMERIZATION: Will not occur

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: None

Section 11: Toxicological Information

HYDROTREATED LIGHT DISTILLATE 64742-47-8

Acute oral toxicity: LD 50 Rat: > 8,000 mg/kg

Acute dermal toxicity: LD 50 Rabbit: > 4,000 mg/kg

Acute inhalation toxicity: LD 50 Rat: > 2,500 ppm, 4 h

HYDROCARBON PROPELLANT 68476-86-8

D-LIMONENE DISTILLATE 5989-27-5

Acute oral toxicity: LD50: >5,000 mg/kg (rabbit)

Acute dermal toxicity: LD50: >1,000 mg/kg (rabbit)

Acute inhalation toxicity: LD50: >5,000 mg/kg (mouse)

Section 12: Ecological Information

If applicable, IARL, NPT and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified in Section III with an "*". Additional ecological information is Not Determined.

Section 13: Disposal Information

Dispose of contents/container in accordance with local regulations.

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which

are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

Section 14: Transportation Information

DOT Proper Shipping Name: UN1950

Aerosol, flammable, (each not exceeding 1L capacity) 2.1

Section 15: Regulatory Information

	CAS#	PEL	TLV
HYDROTREATED LIGHT DISTILLATE	64742-47-8	NONE ESTABLISHED BY OSHA	NONE ESTABLISHED BY OSHA
HYDROCARBON PROPELLANT	68476-86-8	NO DATA	NO DATA
D-LIMONENE DISTILLATE	5989-27-5	NOT ESTABLISHED	NOT ESTABLISHED

If applicable, IARC, NTP and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified above with an "*"

All material components are listed in the U.S. TSCA inventory.

Section 16: Other Information

Consumer Product Safety Act Certification.

This product was evaluated by the Company listed above and is certified to be in compliance with the provisions of the Consumer Product Safety Act, the Federal Hazardous Substances Act, and the Poison Prevention Packaging Act, as applicable. This product was manufactured at the location identified on the SDS. The date of manufacture is stamped on the product container. No testing is required to certify compliance with the above mentioned regulation.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.