SDS PREP DATE: 5/5/2023

SDS REVISION DATE: 5/5/2023

Product ID: GMS1403A

0011



GMS Industrial Supply, Inc. 212 Denn Lane, Virginia Beach, VA 23462 (855) GRN-OGER • www.GreenOger.com

24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

This Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this SDS must be given to the buyer or the information incorporated in your SDS.

# Section 1: Company and Product Identification \_

Product ID: GMS1403A

Product Name: FULL CONTACT

Intended Use: ENERGIZED ELECTRICAL CLEANER

#### **GMS Industrial Supply, Inc.**

212 Denn Lane, Virginia Beach, VA 23462 (855) GRN-OGER

24-Hour Emergency Telephone: 1 (800) 424-9300 CHEMTREC

# Section 2: Hazard(s) Identification

Product Signal Word: DANGER

**Physical Hazard Classification:** Aerosols, Category 3

Contains gas under pressure; may explode if heated.

### **Physical Hazard Precautionary Statements:**

Do not pierce or burn, even after use.

Do not expose to temperatures exceeding 50 °C/122°F.

# **Health Hazard Classification(s):**

Acute Toxicity - Oral - Level 4

#### **Health Hazard Statements:**

Acute Toxicity - Dermal - Level 4

Acute Toxicity - Inhalation - Level 5

Skin Corrosion/Irritation -Level 3

Eye Damage/Irritation -Level 2B

Mutagenicity -Cell -Level 1

Carcinogenicity - Level 2

Toxic to Reproduction - Level 1

Harmful if swallowed.

Harmful in contact with skin.

Causes mild skin irritation.

Causes eye irritation.

SDS PREP DATE: 5/5/2023







1

SDS REVISION DATE: 5/5/2023

SDS PREP DATE: 5/5/2023

SDS REVISION DATE: 5/5/2023

Product ID: GMS1403A

0011

(855) GRN-OGER • www.GreenOger.com

212 Denn Lane, Virginia Beach, VA 23462

GMS Industrial Supply, Inc.

24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

May be harmful if inhaled.

May cause genetic defects.

Suspected of causing cancer.

May damage fertility or the unborn child.

#### First-Aid Statement(s):

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

IF ON SKIN: Wash with plenty of water.

IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

Call a POISON CENTER/doctor/physician if you feel unwell.

See Section 12 if specific treatment is applicable.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

#### Handling and Storage Statement(s):

Use personal protective equipment as required.

Store locked up.

### Exposure Control / Personal Protection Statement(s):

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wash hands and exposed areas thoroughly after handling.

Do no eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

### Disposal Statement(s):

Dispose of contents/container in accordance with local regulations.

## **Section 3: Product Composition**

	CAS#	% Range		PEL	TLV
TETRACHLOROETHYLENE *	127-18-4	95%	99%	25 PPM	25 PPM
CARBON DIOXIDE	124-38-9	1%	5%	5,000 ppm	5,000 ppm; 30,000 ppm, 15

Specific chemical identity and exact percentages are withheld as Trade Secret.

# Section 4: First-Aid Measures

SDS PREP DATE: 5/5/2023

0011

SDS REVISION DATE: 5/5/2023

Product ID: GMS1403A

GMS1403A

GMS Industrial Supply, Inc. 212 Denn Lane, Virginia Beach, VA 23462 (855) GRN-OGER • www.GreenOger.com 24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

3

24 Hour Emergency Telephoner (666) 42

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

IF ON SKIN: Wash with plenty of water.

IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

Call a POISON CENTER/doctor/physician if you feel unwell.

See Section 12 if specific treatment is applicable.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

GENERAL: This material is an aspiration hazard and defats the skin. Breathing vapors of high concentrations may cause CNS depression.

EYE CONTACT: Slightly irritating but does not injure eye tissue.

SKIN CONTACT: Low order of toxicity. Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

INHALATION: High vapor/aerosol concentrations (greater than approximately 100 ppm) are irritating to the eyes and the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

INGESTION: Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly minimal toxicity.

#### FIRST AID

EYE CONTACT: Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

SKIN CONTACT: Flush with large amounts of water; use soap if available. Remove grossly contaminated clothing, including shoes, and launder before reuse.

INHALATION: Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention

INGESTION: If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

### **PRECAUTIONS**

SPECIAL PRECAUTIONS: Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

PERSONAL PROTECTION: For open systems where contact is likely, wear safety glasses with side shields, long sleeves, and chemical resistant gloves. Where concentrations in air may exceed the limits, work practice or other means of exposure reduction are not adequate, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.

VENTILATION: The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated.

# Section 5: Fire-Fighting Measures \_\_\_\_\_

FIRE AND EXPLOSION HAZARDS: This product releases Flammable Vapors at well below ambient temperatures and readily forms flammable mixtures with air exposed to an ignition source. It will burn in the open or be explosive in confined spaces. Its vapors are heavier than air and may travel long distances to a point of ignition, and then flash back. Alkaline/chlorine gas mixtures have produced explosions.

EXTINGUISHING MEDIA: Dry Chemical. CO2. Halogenated Extinguishing Agent. Stop Gas Flow.

SPECIAL FIREFIGHTING PROCEDURES: Gas fires should not be extinguished unless the gas flow can be stopped immediately. Allow the fire to burn itself out. If the source cannot be shut off immediately, all equipment and surfaces exposed to the fire should be cooled with water to prevent over-heating flash-backs, or explosions. Control fire until gas supply can be shut off. Use proper protective equipment. Use fresh air respirator when exposure to hazardous concentrations of toxic gases is possible.

SDS PREP DATE: 5/5/2023

0011

SDS REVISION DATE: 5/5/2023

Product ID: GMS1403A

MS1403A

GMS Industrial Supply, Inc. 212 Denn Lane, Virginia Beach, VA 23462 (855) GRN-OGER • www.GreenOger.com 24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

FIRE FIGHTING: Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boiling over. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

## Section 6: Accidental Release Measures

STEPS TO BE TAKEN IN CASE CONTAINER IS PUNCTURED AND MATERIAL IS RELEASED:

Clean up area by mopping or with absorbent materials and place in closed container for disposal. Consult Federal, State, and local disposal authorities.

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

# Section 7: Handling and Storage \_\_\_\_\_

Use personal protective equipment as required.

Store locked up.

VENTILATION REQUIREMENT: Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

EYES: Face shield and goggles or chemical goggles should be worn.

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

# Section 8: Exposure Control / Personal Protection \_\_\_\_\_

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wash hands and exposed areas thoroughly after handling.

Do no eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

VENTILATION REQUIREMENT: Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

SDS PREP DATE: 5/5/2023

0011

SDS REVISION DATE: 5/5/2023

Product ID: GMS1403A

GMS Industrial Supply, Inc. 212 Denn Lane, Virginia Beach, VA 23462 (855) GRN-OGER • www.GreenOger.com 24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

EYES: Face shield and goggles or chemical goggles should be worn.

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

## Section 9: Product Properties\_\_\_\_\_

Flash Point (CCP): N/A

Boiling Point for Product: 185°C

Vapor Pressure for Product: 8 mm Hg @ 20°C

Vapor Density for Product: >1

Specific Gravity: 1.44

V.O.C.: 0

Water Solubility: NIL

Appearance: CLEAR SOLVENT SPRAY

PH: N/D

# **Section 10: Stability and Reactivity**

STABILITY: Stable

CONDITIONS TO AVOID: Temperatures above 130 degree F.

HAZARDOUS POLYMERIZATION: Will not occur

 ${\tt MATERIALS\ AND\ CONDITIONS\ TO\ AVOID\ INCOMPATIBILITY:\ Strong\ oxidizing\ agents}$ 

HAZARDOUS DECOMPOSITION PRODUCTS: None

# Section 11: Toxicological Information\_

TETRACHLOROETHYLENE \* 127-18-4

Acute oral toxicity (LD50): 2629 mg/kg [Rat]. Acute dermal toxicity (LD50): >3228 mg/kg [Rabbit]. Acute toxicity of the vapor (LC50): 5200 4 hours [Mouse].

Chronic Effects on Humans:

CARCINOGENIC EFFECTS: Classified A3 (Proven for animal.) by ACGIH. Classified 2A (Probable for human.) by IARC, 2

(Some evidence.) by NTP. MUTAGENIC EFFECTS: Mutagenic for bacteria and/or yeast. May cause damage to the following organs: kidneys, liver, peripheral nervous system, upper respiratory tract, skin, central nervous system (CNS).

Other Toxic Effects on Humans:

Hazardous in case of skin contact (irritant), of inhalation. Slightly hazardous in case of skin contact (permeator), of ingestion.

Special Remarks on Toxicity to Animals:

Lowest Published Lethal Dose/Conc: LDL [Rabbit] - Route: Oral; Dose: 5000 mg/kg LDL [Dog] - Route: Oral; Dose: 4000 mg/kg

LDL [Cat] - Route: Oral; Dose: 4000 mg/kg Special Remarks on Chronic Effects on Humans:

SDS PREP DATE: 5/5/2023

0011

SDS REVISION DATE: 5/5/2023

Product ID: GMS1403A

GMS Industrial Supply, Inc. 212 Denn Lane, Virginia Beach, VA 23462 (855) GRN-OGER • www.GreenOger.com 24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

May cause adverse reproductive effects and birth defects(teratogenic). May affect genetic material (mutagenic). May cause cancer. Special Remarks on other Toxic Effects on Humans:

Acute Potential Health Effects: Skin: Causes skin irritation with possible dermal blistering or burns. Symptoms may include redness, itching, pain, and possible dermal blistering or burns. It may be absorbed through the skin with possible systemic effects. A single prolonged skin exposure is not likely to result in the material being absorbed in harmful amounts. Eyes: Contact causes transient eye irritation, laceration. Vapors cause eye/conjunctival irritation. Symptoms may include redness and pain. Inhalation: The main route to occupational exposure is by inhalation since it is readily absorbed through the lungs. It causes respiratory tract irritation, . It can affect behavior/central nervous system (CNS depressant and anesthesia ranging from slight inebriation to death, vertigo, somnolence, anxiety, headache, excitement hallucinations, muscle incoordination, dizziness, lightheadness, disorientation, seizures, emotional instability, stupor, coma). It may cause pulmonary edema

Ingestion: It can cause nausea, vomiting, anorexia, diarrhea, bloody stool. It may affect the liver, urinary system (proteinuria, hematuria, renal failure, renal tubular disorder), heart (arrhythmias). It may affect behavior/central nervous system with symptoms similar to that of inhalation. Chronic Potential Health Effects: Skin: Prolonged or repeated skin contact may result in excessive drying of the skin, and irritation. Ingestion/Inhalation: Chronic exposure can affect the liver(hepatitis,fatty liver degeneration), kidneys, spleen, and heart (irregular heartbeat/arrhythmias, cardiomyopathy, abnormal EEG), brain, behavior/central nervous system/peripheral nervous system (impaired memory, numbness of extremeties, peripheral neuropathy).

# Section 12: Ecological Information \_\_\_\_\_

TETRACHLOROETHYLENE \* 127-18-4

#### **Ecotoxicity:**

Ecotoxicity in water (LC50): 18.4 mg/l 96 hours [Fish (Fatthead Minnow)]. 18 mg/l 48 hours [Daphnia (daphnia)]. 5 mg/l 96 hours [Fish (Rainbow Trout)]. 13 mg/l 96 hours [Fish (Bluegill sunfish)].

### **Products of Biodegradation:**

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

### **Toxicity of the Products of Biodegradation:**

The product itself and its products of degradation are not toxic.

If applicable, IARL, NPT and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified in Section III with an "\*". Additional ecological information is Not Determined.

# Section 13: Disposal Information

Dispose of contents/container in accordance with local regulations.

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

### Section 14: Transportation Information\_

DOT Proper Shipping Name: UN1950

Aerosols, non-flammable, (each not exceeding 1L

capacity) 2.2

## Section 15: Regulatory Information\_

CAS# PEL TLV

TETRACHLOROETHYLENE \* 127-18-4 25 PPM 25 PPM 25 PPM

CARBON DIOXIDE 124-38-9 5,000 ppm 5,000 ppm; 30,000 ppm, 15

State of California SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986.

SDS PREP DATE: 5/5/2023

0011

SDS REVISION DATE: 5/5/2023

Product ID: GMS1403A

GMS Industrial Supply, Inc. 212 Denn Lane, Virginia Beach, VA 23462 (855) GRN-OGER • www.GreenOger.com ency Telephone: (800) 424-9300 CHEMTREC

24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

WARNING: IN ACCORDANCE WITH PROP 65, THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS AND OTHER REPRODUCTIVE HARM.

If applicable, IARL, NPT and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified above with an "\*"

All material components are listed in the U.S. TSCA inventory.

## **Section 16: Other Information**

Consumer Product Safety Act Certificaton.

This product was evaluated by the Company listed above and is certified to be in compliance with the provisions of the Consumer Product Safety Act, the Federal Hazardous Substances Act, and the Poison Prevention Packaging Act, as applicable. This product was manufactured at the location identified on the SDS. The date of manufacture is stamped on the product container. No testing is required to certify compliance with the above mentioned regulation.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.