SAFETY DATA SHEET



SDS REVISION DATE: February 10, 2020

Product ID: GMS1104A

0024

24-Hour Emergency Telephone: 1-800-424-9300 CHEMTREC

GMS Industrial Supply, Inc.

212 Denn Lane, Virginia Beach, VA 23462

(855) GRN-OGER • www.GreenOger.com

SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: Orange-U-Glad PRODUCT NUMBER: GMS1104A RECOMMENDED USE: Degreaser RESTRICTIONS ON USE: None Known COMPANY NAME: GMS Industrial Supply, Inc. COMPANY ADDRESS: 212 Denn Lane, Virginia Beach, VA 23462 COMPANY PHONE: 855-476-6437 EMERGENCY PHONE: 1-800-424-9300 CHEMTREC

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 1

Liquefied Gas

Eye Irritant: Category 2A

Aspiration Hazard: Category 1

HAZARD STATEMENT(S): DANGER: Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated. Causes eye irritation. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Dispose of contents/container in accordance with local, state, and federal law.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS			
HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT	
Diethylene Glycol n-Butyl Ether	112-34-5	1-10%	
Propane/n-Butane	68476-86-8	3-7%	
Distillates petroleum, hydrotreated light	64742-47-8	1-5%	
Alcohols, C6-12, ethoxylated propxylated	68937-66-6	1-3%	

SECTION IV - FIRST AID MEASURES

EYES: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

INHALATION: Move to fresh air.

SKIN: Wash thoroughly with soap and water.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

CHRONIC HEALTH HAZARDS: May be toxic to kidneys and liver.

NOTE TO PHYSICIAN: There is no specific treatment regimen. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, foam, or Carbon Dioxide (CO₂).

UNSUITABLE EXTINGUISHING MEDIA: N/A

SPECIAL FIRE FIGHTING PROCEDURES: Wear SCBA in fire situations. Use water spray to cool containers exposed to fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Absorb spill with non-combustible material such as vermiculite, sand or earth.

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not puncture container, wrap container and place in trash collection.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use.

OTHER PRECAUTIONS: Keep out of the reach of children.

INCOMPATIBILITY: Strong oxidizing agents, strong reducing agents, acids.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Diethylene Glycol n-Butyl Ether	Not Established	25 ppm
Propane/n-Butane	1000 ppm	1000 ppm
Distillates petroleum, hydrotreated light	5 mg/m3	5 mg/m3
Alcohols, C6-12, ethoxylated propxylated	Not Established	Not Established

ENGINEERING CONTROLS / VENTILATION: Local ventilation/exhaust may be needed in confined spaces

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved organic vapor respiratory protection if listed exposure limits (section VIII) are exceeded.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves **ADDITIONAL MEASURES:** Wash hands thoroughly after handling.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: White Foam **ODOR:** Citrus scent **ODOR THRESHOLD:** 1ppm **pH:** 11-12 MELTING POINT/FREEZING POINT: N/D **INITIAL BOILING POINT AND BOILING RANGE:** > 212°F (100°C) FLASH POINT: N/D **EVAPORATION RATE:** Slow FLAMMABILITY(solid/gas): Extremely Flammable Aerosol **UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:** LOWER FLAMMABILITY LIMIT: N/D **UPPER FLAMMABILITY LIMIT: N/A** EXPLOSIVE LIMIT LOWER (%): N/D EXPLOISVE LIMIT UPPER (%): N/D VAPOR PRESSURE (mm Hg): N/D VAPOR DENSITY (AIR=1): N/D

RELATIVE DENSITY (H2O=1): 0.90 - 1.00 **SOLUBILITY(IES):** 92% PARTITION COEFFICIENT: n-OCTANOL/WATER (Kow): N/D AUTOIGNITION TEMPERATURE: N/D **DECOMPOSITION TEMPERATURE: N/D** VISCOSITY: N/D

SECTION X - STABILITY AND REACTIVITY

REACTIVITY: None Known **CHEMICAL STABILITY: Stable POSSIBLE HAZARDOUS REACTIONS:** None Known **CONDITIONS TO AVOID:** Excessive heat. INCOMPATIBLE MATERIALS: Strong oxidizing agents, strong reducing agents, acids. HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon

SECTION XI - TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Diethylene Glycol n-Butyl Ether (112-34-5) LD₅₀ (Oral, Rat): 3950 - 9740 mg/kg, (Mouse) 12,400 mg/kg, (Guinea Pig) 3000 - 4970 mg/kg, (Rabbit) 4450 mg/kg; LD₅₀ (Skin, Rabbit): 10,300 mg/kg, (Guinea Pig) 31,700 mg/kg, (Mouse & Rat) 5940 mg/kg; LC₅₀ (Inhalation, Rat): 960 ppm Distillates (petroleum), hydrotreated light (64742-47-8) LD₅₀ (Oral, Rat) >5000 mg/kg; LD₅₀ (Dermal, Rabbit) >2000 mg/kg **ROUTES OF ENTRY:** Eyes, Ingestion, Inhalation, Skin EYES: May cause irritation, redness. **INGESTION:** May cause gastrointestinal irritation, nausea, diarrhea, vomiting. **INHALATION:** Causes mild irritation to the respiratory tract. SKIN: May cause irritation, localized defatting. MEDICAL CONDITION AGGRAVATED: None known ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision CHRONIC HEALTH HAZARDS: May be toxic to kidneys and liver.

CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

SECTION XII – ECOLOGICAL INFORMATION

ECOTOXICITY: Diethylene Glycol n-Butyl Ether (112-34-5) LC₅₀ (Lepomis macrochirus, 96hr) 1,300 mg/L; LC₅₀ (Leuciscus idus, 48hr) > 1,000 mg/L; EC₅₀ (Daphnia magna, 48hr) > 100 mg/L; IC₅₀ (Green Algae, 24hr) 100 mg/L; LC₅₀ (Pseudomonas Putida, 16hr) 1,170 mg/L Distillates (petroleum), hydrotreated light (64742-47-8) Not toxic to aquatic organisms (fish, daphnia,

algae) up to water solubility. May adsorb to sediments and possibly cause toxics effects to organisms.

PERSISTENCE AND DEGRADABILITY: This product is biodegradable.

BIOACCUMULATIVE POTENTIAL: This product is not expected to bioaccumulate.

MOBILITY IN SOIL: This product is mobile in soil.

OTHER ADVERSE EFFECTS: None Known

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with local, state and federal regulations. Do not puncture container, wrap container and place in trash collection.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty. HAZARD CLASS/DIVISION: 2.1 UN/NA NUMBER: UN 1950 **PACKING GROUP:** N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, flammableHAZARD CLASS/DIVISION: 2.1UN/NA NUMBER:UN 1950PACKING GROUP:N/A

SHIPPING BY WATER:VESSEL (IMO/IMDG)PROPER SHIPPING NAME:Acrosols, Ltd. Qty.HAZARD CLASS/DIVISION:2.1UN/NA NUMBER:UN 1950PACKING GROUP:N/AENVIRONMENTAL HAZARDS WATER:N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt. CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): None SARA 311/312 HAZARD CATEGORIES: None SARA 313 REPORTABLE INGREDIENTS: Diethylene Glycol n-Butyl Ether (DB) (112-34-5) **CLEAN WATER ACT:** None STATE REGULATIONS: California Proposition 65: None Distillates, Petroleum, Hydrotreated, Light (64742-47-8) RTK - PA, NJ, RI Diethylene Glycol n-Butyl Ether (112-34-5) RTK - PA, NJ INTERNATIONAL REGULATIONS: Diethylene Glycol n-Butyl Ether (112-34-5): European Union - EINECS, Australia - AICS, Japan - ENCS, Korean - ECL, (WHMIS) Canada **VOLATILE ORGANIC COMPOUNDS (VOC): 9.7% NFPA HEALTH:** HMIS HEALTH: 1 NFPA FLAMMABILITY: 1 HMIS FLAMMABILITY: 2 **NFPA REACTIVITY:** 0 **HMIS REACTIVITY:** 0 **NFPA OTHER:** None **HMIS PROTECTION:** Α

SECTION XVI - OTHER INFORMATION

Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purpose of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

Revision Date: February 10, 2020