

SAFETY DATA SHEET

SDS REVISION DATE: 02/13/2026

Product ID: GMS1304A

0024

GMS Industrial Supply, Inc.

212 Denn Lane, Virginia Beach, VA 23462

(855) GRN-OGER • www.GreenOger.com

24-Hour Emergency Telephone: 1-800-424-9300 CHEMTREC

SECTION I - IDENTIFICATION

Product ID: GMS1304A
Product Name: Slick Stick
Revision Date: Feb 13, 2026
Company: GMS INDUSTRIAL SUPPLY, INC.
Address: 212 DENN LN - VIRGINIA BEACH, VA 23462
Emergency Phone: Chemtrec 1-800-424-9300
Information Phone Number: 757-473-1467
Fax: 757-337-3734
Product/Recommended Uses: Gel Lubricant

Date Printed: Feb 13, 2026



SECTION II - HAZARDS IDENTIFICATION

CLASSIFICATION: Aerosols Category 1

Eye Irritant: Category 2A

Specific Target Organ Toxicity (Repeated Exposure): Category 2

Specific Target Organ Toxicity (Single Exposure): Category 3

Reproductive Toxicity: Category 2

Aspiration Hazard: Category 1

HAZARD STATEMENT(S): DANGER: Extremely Flammable Aerosol. Pressurized container: May burst if heated. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No Smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn even after use. Protect from sunlight. Do not expose to temperature exceeding 50°C/ 122°F. Obtain, read and follow all safety instructions before use. Do not breathe mist, vapor, or spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves, protective clothing, and eye protection. **IF ON SKIN:** wash with plenty of water. If skin irritation occurs: Get medical help. Take off contaminated clothing and wash it before reuse. **IF EXPOSED OR CONCERNED:** Get emergency medical help immediately. Use only outdoors or in a well-ventilated area. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell. **IF SWALLOWED:** Get emergency medical help immediately. Do NOT induce vomiting. Store in a well-ventilated place. Dispose of contents and container in accordance with local, state, and national regulations.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Distillates (petroleum), hydrotreated light	64742-47-8	10-30%
Acetone	67-64-1	10-30%
Hexane	110-54-3	5-10%
Propane	74-98-6	5-10%
Butane	106-97-8	5-10%

Trade Secret Information: A specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION IV - FIRST AID MEASURES

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: Aspiration hazard. Rinse mouth with water. Do not induce vomiting unless directed by medical authority. Seek medical attention immediately.

INHALATION: Remove to fresh air. If not breathing administer artificial respiration. If breathing is difficult give oxygen. Seek medical attention immediately.

Safety Data Sheet

Slick Stick

SKIN: Immediately wash with soap and water for 15 minutes. Continue rinsing skin as needed. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation develops.

ACUTE HEALTH HAZARDS: Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

CHRONIC HEALTH HAZARDS: May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child.

NOTE TO PHYSICIAN: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Carbon Dioxide and dry chemical

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Avoid breathing smoke, fumes, and decomposition products. Cool fire exposed containers with water fog to prevent bursting.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Eliminate all sources of ignition. absorb liquid with non-combustible material like vermiculite, sand or earth and clean up with mop or rag.

WASTE DISPOSAL: Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Do not pierce or burn, even after use.

OTHER PRECAUTIONS: Keep out of the reach of children.

INCOMPATIBILITY: Strong alkalis, oxidizers, bases, reactive metals, and natural rubber

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Isoparaffinic Petroleum Distillate	Not Established	200 mg/m ³
Acetone	750 ppm	500 ppm
Hexane	500 ppm	50 ppm
Propane	1000 ppm	1000 ppm
Butane	1000 ppm	1000 ppm

ENGINEERING CONTROLS / VENTILATION: Use only outdoors or in a well-ventilated area.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved organic vapor respiratory protection if listed exposure limits (section VIII) are exceeded.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses, chemical resistant gloves, and protective clothing.

ADDITIONAL MEASURES: Wash hands thoroughly after handling.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Tan Spray

ODOR: Acetone

ODOR THRESHOLD: N/D

pH: N/A

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: > 65°C (150°F)

FLASH POINT: > -23°C (-9°F)

EVAPORATION RATE: >3 Fast

FLAMMABILITY(solid/gas): Extremely Flammable Aerosol

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

Safety Data Sheet
Slick Stick

LOWER FLAMMABILITY LIMIT: N/D
UPPER FLAMMABILITY LIMIT: N/D
EXPLOSIVE LIMIT LOWER (%): N/D
EXPLOSIVE LIMIT UPPER (%): N/D
VAPOR PRESSURE (mm Hg): N/D
VAPOR DENSITY (AIR=1): N/D
RELATIVE DENSITY (H₂O=1): 0.78 - 0.82
SOLUBILITY(IES): 0%
PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D
AUTOIGNITION TEMPERATURE: N/D
DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY

REACTIVITY: Certain plastics, rubber, strong oxidizers
CHEMICAL STABILITY: Stable under normal storage conditions.
POSSIBLE HAZARDOUS REACTIONS: None Known
CONDITIONS TO AVOID: Temperatures greater than 122°F and sources of ignition.
INCOMPATIBLE MATERIALS: Strong alkalis, oxidizers, bases, reactive metals, and natural rubber
HAZARDOUS DECOMPOSITION PRODUCTS: Stable under normal storage conditions.

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Acetone (67-64-1) LD₅₀ (Oral, Rabbit) 5340 mg/kg; LD₅₀ (Dermal, Rabbit) 20000 mg/kg
ROUTES OF ENTRY: Eyes, Inhalation, Skin
EYES: Causes irritation, redness, tearing, pain, blurred vision.
INGESTION: Aspiration hazard. If ingested, material may be aspirated into the lungs. May cause gastrointestinal irritation, nausea, diarrhea, vomiting.
INHALATION: Causes dizziness, excessive or prolonged exposure may cause unconsciousness.
SKIN: May cause localized defatting, irritation, dermatitis.
MEDICAL CONDITION AGGRAVATED: Excessive exposure will aggravate pre-existing skin disorders, respiratory, liver, kidney, cardiovascular or pulmonary illnesses.
ACUTE HEALTH HAZARDS: Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
CHRONIC HEALTH HAZARDS: May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child.
CARCINOGENICITY: OSHA: No ACGIH: N/A NTP: No IARC: N/A OTHER: CA Prop 65

SECTION XII – ECOLOGICAL INFORMATION

ECOTOXICITY: Not Established
PERSISTENCE AND DEGRADABILITY: Component or components of this product are not biodegradable.
BIOACCUMULATIVE POTENTIAL: Component or components of this product are not expected to bioaccumulate.
MOBILITY IN SOIL: This product is mobile in soil.
OTHER ADVERSE EFFECTS: This material is toxic to aquatic life.

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.
RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950
PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, flammable

Safety Data Sheet
Slick Stick

HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950
PACKING GROUP: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG)
PROPER SHIPPING NAME: Aerosols
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950
PACKING GROUP: N/A

ENVIRONMENTAL HAZARDS WATER: Marine Pollutant

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Hexane (110-54-3) Reportable Quantity = 5,000 lbs. Acetone (67-64-1) Reportable Quantity = 5,000 lbs

SARA 311/312 HAZARD CATEGORIES: Acute Health, Fire

SARA 313 REPORTABLE INGREDIENTS: None

STATE REGULATIONS: California Proposition 65: WARNING: This product can expose you to chemicals including Hexane, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Propane (74-98-6): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CT, DE, MA, MN, NJ, PA. Acetone (67-64-1): Included on State Hazardous Substances Inventories, Right-to-Know lists and/or Air Quality or Air Pollutants lists for the following states: CA, DE, ID, ME, MA, MN, NJ, PA, RI, WA.

INTERNATIONAL REGULATIONS: Propane (74-98-6): Listed or exempted on the AICS (Australian Inventory of Chemical Substances), Canadian DSL (Domestic Substances List), IECSC (Inventory of Existing Chemical Substances Produced or Imported in China), EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances), Japanese ENCS (Existing & New Chemical Substances), Korean ECL (Existing Chemicals List), NZIoC (New Zealand Inventory of Chemicals), and PICCS (Philippines Inventory of Chemicals and Chemical Substances).

VOLATILE ORGANIC COMPOUNDS (VOC): 24.9%

NFPA HEALTH:	3	HMIS HEALTH:	3
NFPA FLAMMABILITY:	3	HMIS FLAMMABILITY:	3
NFPA REACTIVITY:	0	HMIS REACTIVITY:	0
NFPA OTHER:	None	HMIS PROTECTION:	C

SECTION XVI - OTHER INFORMATION

PREPARATION BY: William Bell

DATE PREPARED: 03/26/2020

REVISION DATE: 02/13/2026

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty expressed or inferred regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.