

SAFETY DATA SHEET

SDS PREP DATE: 5/5/2023

SDS REVISION DATE: 5/5/2023

**Product ID: GMS2008A
00011**



GMS Industrial Supply, Inc.
212 Denn Lane, Virginia Beach, VA 23462
(855) GRN-OGER • www.GreenOger.com

24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

This Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this SDS must be given to the buyer or the information incorporated in your SDS.

Section 1: Company and Product Identification

Product ID: GMS2008A

Product Name: Choke-N-Hose

Intended Use: CARB CLEANER

GMS Industrial Supply, Inc.

212 Denn Lane,

Virginia Beach, VA 23462

(855) GRN-OGER

24-Hour Emergency Telephone: 1 (800) 424-9300 CHEMTREC

Section 2: Hazard(s) Identification

Product Signal Word:

Physical Hazard Classification: Flammable Liquid, Category 1
Extremely flammable liquid and vapour.

Physical Hazard Precautionary Statements:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Keep cool.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): wash contaminated area thoroughly.

Rinse skin with water/shower.

Take off immediately all contaminated clothing.

In case of fire: Contact authorities, avoid breathing fumes and smoke.

Use appropriate media to extinguish.

Store in a well-ventilated place.

Dispose of contents/container in accordance with local regulations.



Health Hazard Classification(s):

Acute Toxicity - Oral - Level 4

SAFETY DATA SHEET

SDS PREP DATE: 5/5/2023

SDS REVISION DATE: 5/5/2023

Product ID: GMS2008A

00011

GMS Industrial Supply, Inc.
212 Denn Lane, Virginia Beach, VA 23462
(855) GRN-OGER • www.GreenOger.com

24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

Health Hazard Statements:

Acute Toxicity - Dermal - Level 4

Acute Toxicity - Inhalation - Level 4

Skin Corrosion/Irritation -Level 3

Eye Damage/Irritation -Level 2A

Carcinogenicity - Level 2

Specific Target Organ Toxicity (Single Exposure) - Level 2

Specific Target Organ Toxicity (Repeated Exposure) - Level 2



Harmful if swallowed.

May be harmful if swallowed and enters airways.

Harmful in contact with skin.

Causes mild skin irritation.

Causes serious eye irritation.

Harmful if inhaled.

Suspected of causing cancer.

May cause damage to organs.

May cause damage to organs through prolonged or repeated exposure.

First-Aid Statement(s):

IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

IF ON SKIN: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

If exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

Call a POISON CENTER/doctor/physician if you feel unwell.

Get medical advice/attention if you feel unwell.

See Section 12 if specific treatment is applicable.

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Handling and Storage Statement(s):

Use personal protective equipment as required.

SAFETY DATA SHEET

SDS PREP DATE: 5/5/2023

SDS REVISION DATE: 5/5/2023

Product ID: GMS2008A

00011

GMS Industrial Supply, Inc.
212 Denn Lane, Virginia Beach, VA 23462
(855) GRN-OGER • www.GreenOger.com

24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

Store locked up.

Exposure Control / Personal Protection Statement(s):

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Avoid breathing dust/fume/gas/mist/vapours/spray.
- Wash hands and exposed areas thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Use personal protective equipment as required.

Disposal Statement(s):

- Dispose of contents/container in accordance with local regulations.

Section 3: Product Composition

	CAS#	% Range		PEL	TLV
ACETONE	67-64-1	85%	95%	TWA 1000 PPM	TWA 750 PPM STEL 1000 PPM
METHYL ALCOHOL *	67-56-1	0%	5%	200 ppm	200 ppm
AROMATIC HYDROCARBON *	108-88-3	1%	10%	TWA OF 100 ppm(375	TWA OF 50 ppm (147 mg/m3)
XYLENE *	1330-20-7	0%	5%	100 ppm	100 ppm
CARBON DIOXIDE	124-38-9	0	5	5,000 ppm	5,000 ppm; 30,000 ppm, 15

Specific chemical identity and exact percentages are withheld as Trade Secret.

Section 4: First-Aid Measures

- IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.
- IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
- IF ON SKIN: Wash with plenty of water.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If exposed or concerned: Get medical advice/attention.
- If exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.
- Call a POISON CENTER/doctor/physician if you feel unwell.
- Get medical advice/attention if you feel unwell.
- See Section 12 if specific treatment is applicable.
- Do NOT induce vomiting.
- If skin irritation occurs: Get medical advice/attention.

SAFETY DATA SHEET

SDS PREP DATE: 5/5/2023

SDS REVISION DATE: 5/5/2023

Product ID: GMS2008A

00011

GMS Industrial Supply, Inc.
212 Denn Lane, Virginia Beach, VA 23462
(855) GRN-OGER • www.GreenOger.com

24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

GENERAL:This material is an aspiration hazard and defats the skin. Breathing vapors of high concentrations may cause CNS depression.

EYE CONTACT: May cause eye injury which may persist for several days. Liquid and vapor in high concentrations, causes irritation, tearing and burning sensation.

SKIN CONTACT: Low order of toxicity. Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

INHALATION: High vapor concentrations (greater than approximately 100 ppm) are irritating to the eyes and the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

INGESTION:May be poisonous or fatal if swallowed. A Small amounts of this product can cause mental sluggishness, nausea and vomiting leading to severe illness, and may produce adverse effects on vision with possible blindness or death if treatment not received.

FIRST AID

EYE CONTACT:Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

SKIN CONTACT: Flush with large amounts of water; use soap if available. Remove grossly contaminated clothing, including shoes, and leather before reuse.

INHALATION: Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention

INGESTION: If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

PRECAUTIONS

SPECIAL PRECAUTIONS:As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

PERSONAL PROTECTION: For open systems where contact is likely, wear safety glasses with side shields, long sleeves, and chemical resistant gloves. Where concentrations in air may exceed the limits, work practice or other means of exposure reduction are not adequate,NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.

VENTILATION: The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated.

Section 5: Fire-Fighting Measures

GENERAL HAZARD:

Flammable liquid, can release vapors that form flammable mixtures at temperatures at or above the flash point. Static Discharge, material can accumulate static charge which can cause an incendiary electrical discharge."Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death. Empty containers should be completely drained, properly bunged and promptly returned to drum re-conditioner, or properly disposed of.

FIRE FIGHTING:

Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boil over. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

HAZARDOUS COMBUSTION PRODUCTS: Fumes, smoke and carbon monoxide.

Section 6: Accidental Release Measures

LAND SPILL: Eliminate sources of ignition. Prevent additional discharge of material, if possible to do so without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting notify the National Response Center. Prevent liquid from entering sewers, watercourses, or low areas. Contain spilled liquid with sand or earth. Do not use combustible materials such as sawdust. Recover by pumping or with a suitable absorbent. Consult an expert on disposal regulations.

WATER SPILL: Eliminate sources of ignition warn occupants and shipping in surrounding and downwind areas of fire and explosion hazard and request all to stay clear. Remove from surface by skimming or with suitable adsorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in non-confined waters. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulation.

SAFETY DATA SHEET

SDS PREP DATE: 5/5/2023

SDS REVISION DATE: 5/5/2023

Product ID: GMS2008A

00011

GMS Industrial Supply, Inc.
212 Denn Lane, Virginia Beach, VA 23462
(855) GRN-OGER • www.GreenOger.com

24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

Section 7: Handling and Storage

Use personal protective equipment as required.

Store locked up.

VENTILATION REQUIREMENT: Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

EYES: Face shield and goggles or chemical goggles should be worn.

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing. Standard work shoes; discard if shoes cannot be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

Section 8: Exposure Control / Personal Protection

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapours/spray.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash hands and exposed areas thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

VENTILATION REQUIREMENT: Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

EYES: Face shield and goggles or chemical goggles should be worn.

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing. Standard work shoes; discard if shoes cannot be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

SAFETY DATA SHEET

SDS PREP DATE: 5/5/2023

SDS REVISION DATE: 5/5/2023

Product ID: GMS2008A

00011

GMS Industrial Supply, Inc.
212 Denn Lane, Virginia Beach, VA 23462
(855) GRN-OGER • www.GreenOger.com

24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

Section 9: Product Properties

Flash Point (CCP): N/D
Boiling Point for Product: N/D
Vapor Pressure for Product: <85 psi @ 65F
Vapor Density for Product: N/D
Specific Gravity: LIQUID .85-.92
V.O.C.: <10% GAL.
Water Solubility: NIL
Appearance: CLEAR SOLVENT SPRAY
PH:

Section 10: Stability and Reactivity

STABILITY: Stable
CONDITIONS TO AVOID INSTABILITY: Not applicable
HAZARDOUS POLYMERIZATION: Will not occur
MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide

Section 11: Toxicological Information

ACETONE 67-64-1

Acute oral toxicity: LD50 Rat: 5,800 mg/kg
Acute inhalation toxicity: LC50 Rat: > 16,000 ppm, 4 h
Acute dermal toxicity: LD50 Rabbit: > 20,000 mg/kg

Single exposure risk: Targets nervous system and may cause drowsiness or dizziness. If a person shows signs of overexposure, remove to fresh air.

METHYL ALCOHOL * 67-56-1

Routes of Entry: Absorbed through skin. Eye contact. Inhalation. Ingestion.

Toxicity to Animals:

WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 5628 mg/kg [Rat]. Acute dermal toxicity (LD50): 15800 mg/kg [Rabbit]. Acute toxicity of the vapor (LC50): 64000 4 hours [Rat].

Chronic Effects on Humans:

MUTAGENIC EFFECTS: Mutagenic for mammalian somatic cells. Mutagenic for bacteria and/or yeast. TERATOGENIC EFFECTS: Classified POSSIBLE for human. Causes damage to the following organs: eyes. May cause damage to the following organs: blood, kidneys, liver, brain, peripheral nervous system, upper respiratory tract, skin, central nervous system (CNS), optic nerve.

Other Toxic Effects on Humans:

Hazardous in case of skin contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).

AROMATIC HYDROCARBON * 108-88-3

Acute oral toxicity: LD50 Rat: 2,600 - 7,500 mg/kg
Acute inhalation toxicity: LC50 Rat: 8,000 ppm, 4 h
Acute dermal toxicity: LD50 Rabbit: 12,124 mg/kg

Reproductive toxicity:

SAFETY DATA SHEET

SDS PREP DATE: 5/5/2023

SDS REVISION DATE: 5/5/2023

Product ID: GMS2008A

00011

GMS Industrial Supply, Inc.
212 Denn Lane, Virginia Beach, VA 23462
(855) GRN-OGER • www.GreenOger.com

24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

Suspected human reproductive toxicant. Lung irritation, chest pain, pulmonary edema, Inhalation studies on toluene have demonstrated the development of inflammatory and ulcerous lesions of the penis, prepuce, and scrotum in animals. Central nervous system Depressant.

XYLENE * 1330-20-7

TWA: 100 ppm

TLV: 100 ppm

Section 12: Ecological Information

ACETONE 67-64-1

Acute and Prolonged Toxicity to Fish

96 h LC 50 Fathead minnow (*Pimephales promelas*), : 8,733 - 9,482 mg/l Mortality

96 h LC 50 Bluegill (*Lepomis macrochirus*), : 8,300 mg/l Mortality

96 h LC 50 Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), : 4,740 - 6,330 mg/l Mortality

Acute Toxicity to Aquatic Invertebrates

No data

Environmental fate and pathways

No data

METHYL ALCOHOL * 67-56-1

Ecotoxicity: Ecotoxicity in water (LC50): 29400 mg/l 96 hours [Fathead Minnow].

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are less toxic than the product itself.

Special Remarks on the Products of Biodegradation:

Methanol in water is rapidly biodegraded and volatilized. Aquatic hydrolysis, oxidation, photolysis, adsorption to sediment, and bioconcentration are not significant fate processes. The half-life of methanol in surface water ranges from 24 hrs. to 168 hrs. Based on its vapor pressure, methanol exists almost entirely in the vapor phase in the ambient atmosphere. It is degraded by reaction with photochemically produced hydroxyl radicals and has an estimated half-life of 17.8 days. Methanol is physically removed from air by rain due to its solubility. Methanol can react with NO₂ in polluted to form methyl nitrate. The half-life of methanol in air ranges from 71 hrs. (3 days) to 713 hrs. (29.7 days) based on photooxidation half-life in air.

AROMATIC HYDROCARBON * 108-88-3

Bioaccumulation

Species: Ide, silver or golden orfe (*Leuciscus idus*)

Exposure time: 3 d

Dose: 0.05 mg/l

Bioconcentration factor (BCF): 94

Method: Not reported

Ecotoxicity effects

Toxicity to fish

96 h LC 50 Rainbow trout, donaldson trout (*Oncorhynchus mykiss*): 5.80 mg/l

Method: Renewal, Mortality

96 h LC 50 Fathead minnow (*Pimephales promelas*): 12.60 mg/l

Method: Static Mortality

Toxicity to daphnia and other aquatic invertebrates.

48 h EC 50 Water flea (*Daphnia magna*): 6.00 mg/l

Method: Static, Intoxication

XYLENE * 1330-20-7

This product is a mobile liquid. This product is non biodegradable. It does not accumulate or biomagnify in the environment.

If applicable, IARL, NPT and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified in Section III with an "*". Additional ecological information is Not Determined.

Section 13: Disposal Information

SAFETY DATA SHEET

SDS PREP DATE: 5/5/2023

SDS REVISION DATE: 5/5/2023

Product ID: GMS2008A
00011

GMS Industrial Supply, Inc.
212 Denn Lane, Virginia Beach, VA 23462
(855) GRN-OGER • www.GreenOger.com

24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

Dispose of contents/container in accordance with local regulations.

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

Section 14: Transportation Information

DOT Proper Shipping Name: UN1950

Aerosols, non-flammable, (each not exceeding 1L capacity) 2.2

Section 15: Regulatory Information

	CAS#	PEL	TLV
ACETONE	67-64-1	TWA 1000 PPM	TWA 750 PPM STEL 1000 PPM
METHYL ALCOHOL *	67-56-1	200 ppm	200 ppm
AROMATIC HYDROCARBON *	108-88-3	TWA OF 100 ppm(375	TWA OF 50 ppm (147 mg/m3)
XYLENE *	1330-20-7	100 ppm	100 ppm
CARBON DIOXIDE	124-38-9	5,000 ppm	5,000 ppm; 30,000 ppm, 15

State of California SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986.

WARNING: IN ACCORDANCE WITH PROP 65, THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS AND OTHER REPRODUCTIVE HARM.

If applicable, IARL, NPT and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified above with an "*"

All material components are listed in the U.S. TSCA inventory.

Section 16: Other Information

Consumer Product Safety Act Certification.

This product was evaluated by the Company listed above and is certified to be in compliance with the provisions of the Consumer Product Safety Act, the Federal Hazardous Substances Act, and the Poison Prevention Packaging Act, as applicable. This product was manufactured at the location identified on the SDS. The date of manufacture is stamped on the product container. No testing is required to certify compliance with the above mentioned regulation.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.