





# SAFETY DATA SHEET

SDS PREP DATE: 5/5/2023

SDS REVISION DATE: 5/5/2023

Product ID: **GMS1404A**



GMS Industrial Supply, Inc.  
212 Denn Lane, Virginia Beach, VA 23462  
(855) GRN-OGER • www.GreenOger.com

**0011**

24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC

P281: Use personal protective equipment as required.

## Disposal Statement(s):

P501: Dispose of contents/container in accordance with local regulations.

## Section 3: Product Composition

	CAS#	% Range		PEL	TLV
HYDROCARBON PROPELLANT	68476-86-8	10%	30%	NO DATA	NO DATA
METHYL ALCOHOL *	67-56-1	10%	20%	200 ppm	200 ppm
		40%	60%	TWA 25 ppm	ACGIH 50 ppm
AROMATIC HYDROCARBON *	108-88-3	1%	5%	TWA OF 100 ppm(375	TWA OF 50 ppm (147 mg/m3)
TALL OIL	61790-12-3	1%	5%	NOT ESTABLISHED	NOT ESTABLISHED
AMMONIUM HYDROXIDE	7664-41-7	1%	5%	50 PPM	35 PPM

Specific chemical identity and exact percentages are withheld as Trade Secret.

## Section 4: First-Aid Measures

IF ON SKIN: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

If exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

Immediately call a POISON CENTER/doctor/physician.

Call a POISON CENTER/doctor/physician if you feel unwell.

See section 12 if specific treatment is applicable.

See Section 12 if specific treatment is applicable.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing.

Wash contaminated clothing before reuse.

GENERAL: This material is an aspiration hazard and defats the skin. Breathing vapors of high concentrations may cause CNS depression.

EYE CONTACT: Slightly irritating but does not injure eye tissue.

SKIN CONTACT: Low order of toxicity. Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

INHALATION: High vapor/aerosol concentrations (greater than approximately 100 ppm) are irritating to the eyes and the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

INGESTION: Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly minimal toxicity.

### FIRST AID

EYE CONTACT: Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

SKIN CONTACT: Flush with large amounts of water; use soap if available. Remove grossly contaminated clothing, including shoes, and launder before reuse.

INHALATION: Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is

# SAFETY DATA SHEET

SDS PREP DATE: 5/5/2023

SDS REVISION DATE: 5/5/2023

Product ID: **GMS1404A**



**GMS Industrial Supply, Inc.**  
212 Denn Lane, Virginia Beach, VA 23462  
(855) GRN-OGER • [www.GreenOger.com](http://www.GreenOger.com)

**0011**

**24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC**

stopped. Keep at rest. Call for prompt medical attention  
INGESTION: If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

## PRECAUTIONS

**SPECIAL PRECAUTIONS:** Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

**PERSONAL PROTECTION:** For open systems where contact is likely, wear safety glasses with side shields, long sleeves, and chemical resistant gloves. Where concentrations in air may exceed the limits, work practice or other means of exposure reduction are not adequate, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.

**VENTILATION:** The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated.

## Section 5: Fire-Fighting Measures

**FIRE AND EXPLOSION HAZARDS:** This product releases Flammable Vapors at well below ambient temperatures and readily forms flammable mixtures with air exposed to an ignition source. It will burn in the open or be explosive in confined spaces. Its vapors are heavier than air and may travel long distances to a point of ignition, and then flash back. Alkaline/chlorine gas mixtures have produced explosions.

**EXTINGUISHING MEDIA:** Dry Chemical. CO<sub>2</sub>. Halogenated Extinguishing Agent. Stop Gas Flow.

**SPECIAL FIREFIGHTING PROCEDURES:** Gas fires should not be extinguished unless the gas flow can be stopped immediately. Allow the fire to burn itself out. If the source cannot be shut off immediately, all equipment and surfaces exposed to the fire should be cooled with water to prevent over-heating flash-backs, or explosions. Control fire until gas supply can be shut off. Use proper protective equipment. Use fresh air respirator when exposure to hazardous concentrations of toxic gases is possible.

**FIRE FIGHTING:** Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boiling over. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

## Section 6: Accidental Release Measures

### STEPS TO BE TAKEN IN CASE CONTAINER IS PUNCTURED AND MATERIAL IS RELEASED:

Clean up area by mopping or with absorbent materials and place in closed container for disposal. Consult Federal, State, and local disposal authorities.

**WASTE DISPOSAL METHOD:** Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

## Section 7: Handling and Storage

Use personal protective equipment as required.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

**VENTILATION REQUIREMENT:** Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

**RESPIRATORY PROTECTION:** Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

**EYES:** Face shield and goggles or chemical goggles should be worn.

# SAFETY DATA SHEET

SDS PREP DATE: 5/5/2023

SDS REVISION DATE: 5/5/2023

Product ID: **GMS1404A**



**GMS Industrial Supply, Inc.**  
212 Denn Lane, Virginia Beach, VA 23462  
(855) GRN-OGER • [www.GreenOger.com](http://www.GreenOger.com)

**0011**

**24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC**

**GLOVES:** Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

**OTHER CLOTHING EQUIPMENT:** Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

**RESPIRATORY PROTECTION:** In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

## Section 8: Exposure Control / Personal Protection

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapours/spray.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash hands and exposed areas thoroughly after handling.

Do no eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

**VENTILATION REQUIREMENT:** Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

**RESPIRATORY PROTECTION:** Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

**EYES:** Face shield and goggles or chemical goggles should be worn.

**GLOVES:** Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

**OTHER CLOTHING EQUIPMENT:** Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

**RESPIRATORY PROTECTION:** In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

## Section 9: Product Properties

Flash Point (CCP): LEVEL 3 AEROSOL, PROPELLENT: -136°F

Boiling Point for Product: N/D

Vapor Pressure for Product: N/D

Vapor Density for Product: N/D

Specific Gravity: 1.13 - 1.16

V.O.C.: 35%

# SAFETY DATA SHEET

SDS PREP DATE: 5/5/2023

SDS REVISION DATE: 5/5/2023

Product ID: **GMS1404A**



**GMS Industrial Supply, Inc.**  
212 Denn Lane, Virginia Beach, VA 23462  
(855) GRN-OGER • [www.GreenOger.com](http://www.GreenOger.com)

**0011**

**24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC**

Water Solubility: NEGLIGIBLE

Appearance: SEMI VISCOUS LIQUID

PH:

## Section 10: Stability and Reactivity

STABILITY: Stable

CONDITIONS TO AVOID: Temperatures above 130 degree F.

HAZARDOUS POLYMERIZATION: Will not occur

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: None

## Section 11: Toxicological Information

HYDROCARBON PROPELLANT 68476-86-8

METHYL ALCOHOL \* 67-56-1

**Routes of Entry:** Absorbed through skin. Eye contact. Inhalation. Ingestion.

### Toxicity to Animals:

WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 5628 mg/kg [Rat]. Acute dermal toxicity (LD50): 15800 mg/kg [Rabbit]. Acute toxicity of the vapor (LC50): 64000 4 hours [Rat].

### Chronic Effects on Humans:

MUTAGENIC EFFECTS: Mutagenic for mammalian somatic cells. Mutagenic for bacteria and/or yeast. TERATOGENIC EFFECTS: Classified POSSIBLE for human. Causes damage to the following organs: eyes. May cause damage to the following organs: blood, kidneys, liver, brain, peripheral nervous system, upper respiratory tract, skin, central nervous system (CNS), optic nerve.

### Other Toxic Effects on Humans:

Hazardous in case of skin contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).

AROMATIC HYDROCARBON \* 108-88-3

**Acute oral toxicity:** LD50 Rat: 2,600 - 7,500 mg/kg

**Acute inhalation toxicity:** LC50 Rat: 8,000 ppm, 4 h

**Acute dermal toxicity:** LD50 Rabbit: 12,124 mg/kg

### Reproductive toxicity:

Suspected human reproductive toxicant. Lung irritation, chest pain, pulmonary edema, Inhalation studies on toluene have demonstrated the development of inflammatory and ulcerous lesions of the penis, prepuce, and scrotum in animals. Central nervous system Depressant.

TALL OIL 61790-12-3

Due to viscosity may serve as an aspiration hazard if liquid enters the lungs. Do not induce vomiting if swallowed.

## Section 12: Ecological Information

METHYL ALCOHOL \* 67-56-1

**Ecotoxicity:** Ecotoxicity in water (LC50): 29400 mg/l 96 hours [Fathead Minnow].

### Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

**Toxicity of the Products of Biodegradation:** The products of degradation are less toxic than the product itself.

### Special Remarks on the Products of Biodegradation:

# SAFETY DATA SHEET

SDS PREP DATE: 5/5/2023

SDS REVISION DATE: 5/5/2023

Product ID: **GMS1404A**



GMS Industrial Supply, Inc.  
212 Denn Lane, Virginia Beach, VA 23462  
(855) GRN-OGER • www.GreenOger.com

**0011**

**24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC**

Methanol in water is rapidly biodegraded and volatilized. Aquatic hydrolysis, oxidation, photolysis, adsorption to sediment, and bioconcentration are not significant fate processes. The half-life of methanol in surfact water ranges from 24 hrs. to 168 hrs. Based on its vapor pressure, methanol exists almost entirely in the vapor phase in the ambient atmosphere. It is degraded by reaction with photochemically produced hydroxyl radicals and has an estimated half-life of 17.8 days. Methanol is physically removed from air by rain due to its solubility. Methanol can react with NO<sub>2</sub> in polluted to form methyl nitrate. The half-life of methanol in air ranges from 71 hrs. (3 days) to 713 hrs. (29.7 days) based on photooxidation half-life in air.

AROMATIC HYDROCARBON \* 108-88-3

### Bioaccumulation

**Species:** Ide, silver or golden orfe (*Leuciscus idus*)

Exposure time: 3 d

Dose: 0.05 mg/l

Bioconcentration factor (BCF): 94

Method: Not reported

Ecotoxicity effects

### Toxicity to fish

96 h LC 50 Rainbow trout, donaldson trout (*Oncorhynchus mykiss*): 5.80 mg/l

Method: Renewal, Mortality

96 h LC 50 Fathead minnow (*Pimephalespromelas*): 12.60 mg/l

Method: Static Mortality

Toxicity to daphnia and other aquatic invertebrates.

48 h EC 50 Water flea (*Daphnia magna*): 6.00 mg/l

Method: Static, Intoxication

If applicable, IARL, NPT and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified in Section III with an "\*". Additional ecological information is Not Determined.

## Section 13: Disposal Information

Dispose of contents/container in accordance with local regulations.

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

## Section 14: Transportation Information

DOT Proper Shipping Name: UN1950

Aerosols,flammable, (each not exceeding 1L  
capacity) 2.1

## Section 15: Regulatory Information

	CAS#	PEL	TLV
HYDROCARBON PROPELLANT	68476-86-8	NO DATA	NO DATA
METHYL ALCOHOL *	67-56-1	200 ppm TWA 25 ppm	200 ppm ACGIH 50 ppm
AROMATIC HYDROCARBON *	108-88-3	TWA OF 100 ppm(375)	TWA OF 50 ppm (147 mg/m3)
TALL OIL	61790-12-3	NOT ESTABLISHED	NOT ESTABLISHED
AMMONIUM HYDROXIDE	7664-41-7	50 PPM	35 PPM

# SAFETY DATA SHEET

SDS PREP DATE: 5/5/2023

SDS REVISION DATE: 5/5/2023

**Product ID: GMS1404A**



**GMS Industrial Supply, Inc.**  
212 Denn Lane, Virginia Beach, VA 23462  
(855) GRN-OGER • [www.GreenOger.com](http://www.GreenOger.com)

**0011**

**24 Hour Emergency Telephone: (800) 424-9300 CHEMTREC**

State of California SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986.

WARNING: IN ACCORDANCE WITH PROP 65, THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS AND OTHER REPRODUCTIVE HARM.

If applicable, IARL, NPT and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified above with an "\*"

All material components are listed in the U.S. TSCA inventory.

## Section 16: Other Information

Consumer Product Safety Act Certificaton.

This product was evaluated by the Company listed above and is certified to be in compliance with the provisions of the Consumer Product Safety Act, the Federal Hazardous Substances Act, and the Poison Prevention Packaging Act, as applicable. This product was manufactured at the location identified on the SDS. The date of manufacture is stamped on the product container. No testing is required to certify compliance with the above mentioned regulation.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.