

SAFETY DATA SHEET



SDS REVISION DATE: 03/17/2025

Product ID: GMS1500A

0029

GMS Industrial
Supply

GMS Industrial Supply, Inc.
212 Denn Lane, Virginia Beach, VA 23462
(855) GRN-OGER • www.GreenOger.com

24-Hour Emergency Telephone: 1-800-424-9300 CHEMTREC

SECTION 1 - Identification

Product ID: GMS1500A **Date Printed:** Mar 17, 2025
Product Name: Stick-Em-Up
Revision Date: Mar 17, 2025
Distributor's Name: GMS INDUSTRIAL SUPPLY, INC.
Address: 212 DENN LN - VIRGINIA BEACH, VA 23462
Emergency Phone: Chemtrec 1-800-424-9300
Information Phone Number: 757-473-1467
Fax: 757-337-3734
Product/Recommended Uses: General Purpose Adhesive

SECTION 2 – Hazard(s) Identification

2.1 Classification of the Substance or Mixture

GHS-US Classification

| | | |
|-------------------------------|------------|------|
| Flammable Gas: | Category 1 | H220 |
| Flammable Aerosol: | Category 2 | H223 |
| Flammable Liquid | Category 2 | H225 |
| Compressed Gas | | H280 |
| Aspiration Hazard: | Category 1 | H304 |
| Skin Irritation: | Category 2 | H315 |
| Serious Eye Damage/Irritation | Category 1 | H319 |
| Respiratory Irritation | Category 3 | H335 |
| Specific Organ Toxicity: | Category 3 | H370 |
| Central Nervous System | | |

2.2 Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US):



GHS07

GHS08

GHS02

GHS04

Signal Word (GHS-US):

Danger

SAFETY DATA SHEET

SDS REVISION DATE: 03/17/2025

Product ID: GMS1500A

Hazard Statements (GHS-US): H220 – Flammable gas.
H223 – Flammable aerosol.
H225 – Flammable liquid.
H280 – Compressed gas.
H304 – May be fatal if swallowed and enters airways.
H315 – Causes skin irritation.
H320 – Causes eye irritation.
H336 – May causes drowsiness and dizziness.
H360 – May cause damage to fertility or the unborn child.
H370/H372 – Causes damage to organs (Central Nervous System).

Precautionary Statements (GHS-US): P103 – Read label before use.
P201 – Obtain special instructions before use.
P202 – Do not handle until all safety precautions have been read and understood.
P210 – Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 – Keep container tightly closed.
P241 – Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242 – Use only non-sparking tools.
P243 – Take precautionary measures against static discharge.
P270 – Do not eat, drink, or smoke when using this product.
P271 – Use only outdoors or in a well-ventilated area.
P314 – Get medical advice/attention if you feel unwell.

Note: This product is a mixture of which there has not been thorough testing and establishment of all the possible health risks of exposure. There may be unknown effects that are not listed.

SECTION 3 – Composition/Information on Ingredients

Substance Type: Mixture

| Name | Product Identifier | % Composition |
|----------------|--------------------|---------------|
| Acetone | CAS: 67-64-1 | Proprietary |
| Butane | CAS 106-97-8 | Proprietary |
| Hexane | CAS: 110-54-3 | Proprietary |
| Methyl Acetate | CAS: 79-20-9 | Proprietary |
| Propane | CAS 74-98-6 | Proprietary |

SECTION 4 –First-Aid Measures

First-Aid Measures After Inhalation: Remove victim to fresh air immediately. If breathing has stopped give artificial respiration. Get medical attention.
First-Aid Measures After Eye Contact: Flush with large amounts of water, lifting upper and lower lids occasionally. Continue for at least 15 minutes. Get medical attention.
First-Aid Measures After Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Get medical attention if irritation persists.

SECTION 5 – Firefighting Measures

5.1 Extinguishing Media

Suitable Extinguishing Media: Preferably: chemical foam. BC powder. Carbon dioxide.
Unsuitable Extinguishing Media: No information available.

5.2 Special Hazards Arising from the Substance or Mixture

SAFETY DATA SHEET

SDS REVISION DATE: 03/17/2025

Product ID: GMS1500A

Fire Hazard: DIRECT FIRE HAZARD: Highly flammable. INDIRECT FIRE HAZARD: Sparks. Vapor.
Explosion Hazard: DIRECT EXPLOSION HAZARD: Possible explosion hazard.
Reactivity: N/A.

5.3 Advice for Firefighters

Firefighting Instructions: Cool tanks/drums with water spray/remove them to safety.
Protection During Firefighting: Heat/Fire exposure: compressed air/oxygen apparatus.

SECTION 6 – Accidental Release Measures

6.1 Personal Precautions, Protective Equipment, and Emergency Procedures

6.1.1. For Non-Emergency Personnel

Protective Equipment: Gloves, protective goggles, protective clothing. Large spills in enclosed spaces: compressed air apparatus.
Emergency Procedures: Keep upwind. Mark the danger area. Consider evacuation. Close doors and windows of the premises. Stop engines and do not smoke. Keep containers closed. Wash contaminated clothes.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.
Emergency Procedures: Ventilate area.

6.2 Environmental Precautions

Prevent spreading in sewers.

6.3 Methods and Material for Containment and Cleaning Up

For Containment: Contain released substance, pump into suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill. Try to reduce evaporation of spill. Dilute combustible gas/vapor with water curtain.
Methods for Cleaning Up: Take liquid spill into inert absorbent material (sand, earth, etc.) Scoop absorbed substance into closing containers. Spill must not return into its original container. Carefully collect the spill/leftovers. Damaged/cooled tanks must be emptied. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

SECTION 7 – Handling and Storage

7.1 Precautions for Safe Handling

Precautions for Safe Handling: Comply with legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Handle uncleaned empty containers as full ones. Do not discharge waste into the drain. Keep away from ignition sources/sparks. Avoid prolonged and repeated contact with skin. Keep container tightly closed. Work under local exhaust/ventilation.
Hygiene Measures: Do not eat, drink, or smoke when using this product. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and when leaving work.

7.2 Conditions for Safe Storage

Storage Conditions: Keep only in original container in a cool, well ventilated place away from: heat sources, incompatible materials. Keep container closed when not in use.
Incompatible Products: Strong acids. Strong Bases.
Incompatible materials: Sources of ignition. Direct sunlight.
Heat-Ignition: KEEP SUBSTANCE AWAY FROM: heat sources, ignition sources.

SAFETY DATA SHEET

SDS REVISION DATE: 03/17/2025

Product ID: GMS1500A

Prohibitions on Mixed Storage: KEEP SUBSTANCE AWAY FROM: oxidizing agents, reducing agents, strong acids, strong bases, halogens, amines.
Packaging Material: SUITABLE MATERIAL: steel, stainless steel, carbon steel, aluminum, iron, copper, nickel, bronze, glass.

SECTION 8 – Exposure Controls/Personal Protection

8.1 Control Parameters

Parameters categorized by component of mixture:

| Component Name | OSHA Permissible Exposure Limit (PEL) (ppm) TWA |
|----------------|---|
| Acetone | 1000 |
| Butane | 800 |
| Hexane | 500 |
| Methyl Acetate | 200 |
| Propane | 1000 |

8.2 Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available within immediate vicinity of any potential exposure.
Personal Protective Equipment: Safety glasses, gloves, protective clothing, face shield. If high gas/vapor concentration occurs, use gas mask with filter suitable for organic vapors.
Eye Protection: Safety Glasses.
Skin and Body Protection: Head/neck protection. Protective clothing.
Respiratory Protection: Wear gas mask with filter suitable for organic vapors if concentration in air exceeds exposure limit.
Other Information: Do not eat, drink, or smoke during use.

SECTION 9 – Physical and Chemical Properties

Appearance: Clear solution.
Physical State: Liquid.
Boiling Point: 100°F/ 37.8°C
Vapor Pressure: 36.7-400 mmHg @70°F/ 21.1°C
Vapor Density: 2-4
% Volatile: 60-70%

Note: Some physical and chemical properties for this mixture have not been established and therefore cannot be accurately recorded.

SECTION 10 – Stability and Reactivity

10.1 Reactivity

Reacts with strong oxidizers. Increased risk of fire.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of Hazardous Reactions

None established.

SAFETY DATA SHEET

SDS REVISION DATE: 03/17/2025

Product ID: GMS1500A

10.4 Conditions to Avoid

Avoid open flames and other high temperatures sources.

10.5 Incompatible Materials

Strong oxidizers, acids, and bases.

10.6 Hazardous Decomposition Products

None established.

SECTION 11 – Toxicological Information

Inhalation: Intentional concentration and inhalation may be harmful or fatal.
Skin Contact: Causes skin irritation.
Eye Contact: Causes eye irritation.
Ingestion: Ingestion is likely to be harmful or have adverse effects.

SECTION 12 – Ecological Information

Please contact Chem Tech at 574-848-1001 for questions.

SECTION 13 – Disposal Considerations

Dispose of contents and containers in accordance with local and regional regulations.

SECTION 14 – Transport Information

Transportation will be handled according to the Department of Transportation guidelines and regulations.

SECTION 15 – Regulatory Information

All matters regarding this mixture will be handled in accordance to the United States federal regulations. Please contact Chem Tech at 574-848-1001 for further questions.

SECTION 16 – Other Information

This Safety Data Sheet was revised on 03/17/2025.

The information included in this SDS is from available and public sources believed to be accurate. No warranty, express or implied, is made and the writer assumes no liability resulting from the use of this SDS. The user must determine the suitability of this information for their application.